

Anti-slip Coating • High Traffic Resistant  
Fast Drying • Epoxy Fortified Acrylic  
Superior Adhesion • Easy Roller Application  
Even Texture Distribution • Fills & Seals Cracks  
For Interior or Exterior Use

**For Use On:** Steps, walkways, patios, recreational areas, pool areas, ramps, tennis courts, high traffic areas or anywhere traction is required.

**Surface Preparation:** Masonry and Concrete - Allow all poured or precast concrete to cure for 28 days. Smooth, troweled concrete must be acid etched. Follow etching directions. Rinse thoroughly and allow to dry completely.

**Previously Painted Substrates** - Wash and rinse surface using The Duke, Cleaner and Degreaser. Remove all loose and flaking paint. Sand all glossy surfaces to a dull appearance then remove sanding debris.

**Uncoated Asphalt Surfaces** - New asphalt must be cured for 14 days (longer during cooler weather). Surface must be free of oil, grease and dirt. Clean surface using a power washer. Dry well.

**Temperature:** Apply when surface temperature is above 10°C/50°F. Do not apply if rain is in the forecast within 24 hours.

**Application rate:** Apply at the rate of 80 sq ft to 100 sq ft per gallon.

**Pre Application Requirements:** Intermix containers if using more than one container. This is particularly important if the TredMax® containers have different batch numbers. **Note:** Batch numbers are located on the top of the lid. TredMax® can be easily applied with a high quality paint brush or 3/8" nap roller.

**Application Directions:** Stir contents well to ensure even dispersion. With a high quality paint brush, pre-apply to small areas such as stairs or edges. Attach Roller cage to extension pole. For main areas, pour TredMax® in a long continuous bead across the short side of the surface being coated. For uniform sheen and texture Roll product uniformly and finish with long, even strokes.

**Dry Time:** Dries to touch in 1 - 2 hours at the median temperature of 21°C/72°F. May be re-coated after 8 hours. No foot traffic for 24 hours.

**Clean up:** Clean tools and equipment immediately after application with soap and warm water.

**Storage:** Keep from freezing.



**Ducan Industries Ltd.**

1920 Broadway St., Port Coquitlam, BC V3C 2N1

Customer Service: **1-800-943-8226**

[www.ducan.com](http://www.ducan.com)



Printed in Canada  
02/2017

# ducan TredMax®

## Tough, Anti-slip Safety Coating



Contains Ceramic Microspheres  
to ensure Consistent, Uniform Texture

Superior Adhesion  
Epoxy Fortified Acrylic  
Tough and Durable



# ducan TredMax®

Tough, Anti-Slip Safety Coating

Uniform Textured Appearance  
Fast Dry • Durable • Easy Application  
Fills and Seals Cracks  
Easy Soap and Water Clean up



## WHY YOU WILL LOVE THE TEXTURE:

Texture additives, like walnut shell, silica sand and crushed glass create an uneven, textured surface.

With Tredmax you get perfectly round **microceramic microspheres**, which act as ball bearings during application. This prompts the texture in the coating to be evenly distributed across the surface. No more uneven streaking or clumps of texture!

Once dried, TredMax® will provide you with the sure footing you require.



TredMax® can be used for interior or exterior concrete, metal or asphalt, to provide a durable, skid-resistant finish.

## Apply to:

Patios • Steps • Walkways • Ramps  
Tennis Courts • High Traffic Areas  
or wherever traction is required.

TredMax® has excellent abrasion resistance to heavy foot traffic and is very resistant to ponding water.

TredMax® has exceptional colour retention, even in bright sunlight conditions.



# ducan TredMax®

Tough, Anti-Slip Safety Coating

## Neutral Tint Base



Light Grey



Tile Red



Chocolate Brown



Medium Grey



Green



White



Battleship Grey



Sandy Beige



Royal Blue

For: Steps • Walkways • Ramps  
Sports Courts • Driveways  
Pool Surrounds • Tennis Courts